




Construction:	Tufted
Density:	6,835
Dye Method:	Solution Dyed
Fiber Type:	Colorstrand® SD Nylon
Gauge:	1/12 (47.00 rows per 10 cm)
Product Type:	Tile
Size:	24" x 24" (.6096 m x .6096 m)
SmokeDensity:	ASTM E 662 Less than 450
Dropped:	No
BackingMaterial:	EcoFlex ICT
Declare:	Yes
FinishedPileThickness:	.079" (2.00 mm)
Flammability:	ASTM E 648 Class 1 (Glue Down)
FootTrafficRecTARR:	Heavy
IAQGreenLabelPlus:	CRI Green Label Plus GLP1098
NSF140:	EcoFlex ICT - NSF 140 Gold
Pattern:	Linear
PileRange:	15
Scale:	Large
RecycledContentTotalWeight:	0.48
RecycledContentPreConsumer:	48%
SoilReleaseTechnology:	Sentry Soil Protection
Static:	AATCC-134 Under 3.5 KV
StitchesPerInch:	12.5 (49.21 per 10 cm)
SurfaceTexture:	Textured Patterned Loop
WeightDensity:	102,531
LaunchYear:	2017
InherentStainResistance:	Topical
Top10Corp:	No
Top10Healthcare:	No
Top10K12:	No
Top10REITI:	No
Top10Gov:	No
Top10SeniorLiving:	No
Top10HigherEd:	No
Top10Retail:	No
Declare Label:	Declared
Installation Method:	Quarter Turn, Monolithic, Brick Ashlar, Vertical Ashlar, Multi Directional
Pattern Repeat:	Not Applicable
Budget:	\$\$
CountryOfOrigin:	Ships from US



7559
Jewel
Quickship Available



7568
Twilight
Quickship Available




7688
Earth
Quickship Available



7879
Dusk
Quickship Available



7927
Shell
Quickship Available



7948
Mist
Quickship Available