


**DESIGN**

Tufted Pile Weight:	<b>22 oz/yd<sup>2</sup> (746 g/m<sup>2</sup>)</b>
Product Type:	<b>Tile</b>
Construction:	<b>Tufted</b>
Minimum Sq. Yd.:	<b>No Minimum</b>
Surface Texture:	<b>Textured Patterned Loop</b>
Gauge:	<b>1/12 (47.00 rows per 10 cm)</b>
Density:	<b>9,000</b>
Weight Density:	<b>198,000</b>
Stitches Per Inch:	<b>10.0 (39.37 per 10 cm)</b>
Finished Pile Thickness:	<b>.088" (2.23 mm)</b>
Dye Method:	<b>Solution Dyed</b>
Backing Material:	<b>EcoFlex ICT</b>
Fiber Type:	<b>Colorstrand® SD Nylon</b>
Pattern Repeat:	<b>Not Applicable</b>
Size:	<b>24" x 24" (.6096 m x .6096 m)</b>
Installation Method:	<b>Quarter Turn, Vertical Ashlar, Brick Ashlar, Monolithic, Multi Directional</b>
Stain Release Technology:	<b>Sentry Plus Stain Protection</b>
Soil Release Technology:	<b>Sentry Soil Protection</b>
Foot Traffic Recommendation TARR:	<b>Severe</b>

**SUSTAINABILITY**


IAQ Green Label Plus:	<b>CRI Green Label Plus GLP1098</b>
Pre-Consumer Recycled Content:	<b>48%</b>
NSF 140:	<b>EcoFlex ICT - NSF 140 Gold</b>
Declare Label:	<b>Declared</b>

**PERFORMANCE**

Static:	<b>AATCC-134 Under 3.5 KV</b>
Flammability:	<b>ASTM E 648 Class 1 (Glue Down)</b>
Smoke Density:	<b>ASTM E 662 Less than 450</b>

**SERVICE**

Warranties:	<b>Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static</b>
-------------	---




**556**  
Foremost  
Quickship Available




**727**  
Priority  
Quickship Available




**848**  
Beginning  
Quickship Available



**869**  
Immediate  
Quickship Available



**959**  
Preference  
Quickship Available



**988**  
Importance  
Quickship Available