



### Healthy Environments Resilient Collection



832  
Agave



878  
Hemp



935  
Twine



955  
Cordage

#### DESIGN

Product Type:	Resilient Sheet
Overall Thickness:	.080" (2.0 mm)
Wear Layer:	20 mil (0.5 mm)
Finish:	Enhanced Urethane
Surface Profile:	Overall Emboss
Pattern Repeat:	39.37" x 39.37", 1Mx1M
Size:	12' width
Roll Size:	50' min - 65' max
Seaming Method:	Mohawk Solid Color Heat Weld Rod or Cold Weld
Installation Method:	Do not reverse sheet for installation
Recommended Adhesive:	Mohawk M95.0 or M99.0 Adhesive for under bed warranty or MS160 Spray Adhesive

#### PERFORMANCE

Construction:	Commercial Grade Heterogeneous Resilient Sheet Non-ortho Phthalate Construction
Classification:	ASTM F - 1303 Type 1, Grade 1, Class A
Thickness:	ASTM F386 - Passes, $\pm .005$ "
Flexibility:	ASTM 137 - Passes
Static Load:	ASTM F970 - Passes, 750 psi Modified
Residual Indentation:	ASTM F1914 - Passes, Average less than 8%
Resistance To Chemicals:	ASTM F925 - Passes, No Change
Resistance To Light:	ASTM F1515 - Passes, $\Delta E \leq 8$
Resistance To Heat:	ASTM F1514 - Passes, $\Delta E \leq 8$
Critical Radiant Flux:	ASTM E648 - Meets, Class 1
Smoke Density:	M E662 - Meets, 450 or less
Electro Static Propensity:	AATCC 134 - Less than 3.5 kV
Wear Layer Thickness:	ASTM 410 - Passes

#### SUSTAINABILITY

Certification:	FloorScore® certified
----------------	-----------------------

#### SERVICE

Warranties:	Limited 10 Year Commercial Warranty
-------------	-------------------------------------