



DESIGN

Tufted Pile Weight:	15 oz/yd ² (509 g/m ²)
Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	5,192
Weight Density:	77,884
Stitches Per Inch:	11.0 (43.31 per 10 cm)
Finished Pile Thickness:	.104" (2.64 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex Matrix
Fiber Type:	Colorstrand® SD Nylon
Pattern Repeat:	Not Applicable
Size:	12" x 36" (.3048 m x .9144 m)
Installation Method:	Half Lap, Plank Half Lap, Herringbone
Stain Release Technology:	EcoSentry Plus Stain Protection
Soil Release Technology:	EcoSentry Soil Protection
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY

IAQ Green Label Plus:	CRI Green Label Plus GLP1171
Pre-Consumer Recycled Content:	52%
NSF 140:	EcoFlex Matrix - NSF 140 Gold
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, 10 Year Limited Static
-------------	---



593
Indigo Ink
Quickship Available



929
Warm Neutral
Quickship Available



937
Wet Cement
Quickship Available



948
Rustic Taupe
Quickship Available



979
Metal Grey
Quickship Available



989
Dark Charcoal
Quickship Available