



959
Silkscreen
Quickship Available

Construction:	Tufted
Density:	7,043
Dye Method:	Precision Dyed Injection
Fiber Type:	Colorstrand® Nylon
Gauge:	1/10 (39.37 rows per 10 cm)
Product Type:	Broadloom
SmokeDensity:	ASTM E 662 Less than 450
Width:	12' width (3.66 m)
Dropped:	No
BackingMaterial:	Weldlok®
Declare:	Yes
FinishedPileThickness:	.184" (4.67 mm)
Flammability:	ASTM E 648 Class 1 (Glue Down)
FootTrafficRecTARR:	Severe
IAQGreenLabelPlus:	CRI Green Label Plus GLP6678
MinSqYard:	50 sq yd minimum
NSF140:	Weldlok - NSF 140 Gold
Pattern:	Geometric
PileRange:	36
Scale:	Large
RecycledContentTotalWeight:	0.33
RecycledContentPreConsumer:	33%
SoilReleaseTechnology:	EcoSentry Soil Protection
Static:	AATCC-134 Under 3.5 KV
StitchesPerInch:	13.3 (52.36 per 10 cm)
SurfaceTexture:	Level Patterned Cut
WeightDensity:	253,565
LaunchYear:	2019
InherentStainResistance:	Topical
Top10Corp:	No
Top10Healthcare:	No
Top10K12:	No
Top10REITI:	No
Top10Gov:	No
Top10SeniorLiving:	No
Top10HigherEd:	No
Top10Retail:	No
Declare Label:	Declared Red List Free
Pattern Repeat:	36" (W) x 36" (L) SM
Budget:	\$\$\$
CountryOfOrigin:	Ships from US