



DESIGN

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	6,316
Weight Density:	189,480
Stitches Per Inch:	13.0 (51.18 per 10 cm)
Finished Pile Thickness:	.171" (4.34 mm)
Dye Method:	Piece Dyed
Backing Material:	Unibond® Plus
Fiber Type:	Fortis™ Nylon
Face Weight:	30.0 oz. per sq. yd. (1017 g/m2)
Pattern Repeat:	2.5" (W) x 4.5" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry
GSA Stain Release Rating:	Pass
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 3802
Pre-Consumer Recycled Content:	21%
NSF 140:	Platinum
Declare Label:	Declared Red List Free

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Limited Unibond® Plus Warranty, Lifetime Static
-------------	---



7128
Spicy Curry




7378
Organic Tomato




7499
Vintage Tokay




7585
Aqueous Spa



7595
Mystic Indigo



7646
Gingko Leaf



7838
Sea Salt



7841
Asian Pear



7848
Bridge Stone



7862
Burled Wood



7875
Raw Earth



7888
Brown Under



7959
Irony Grey



7989
Black Ice