



DESIGN

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Heathered Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	8,216
Weight Density:	136,862
Stitches Per Inch:	11.0 (43.31 per 10 cm)
Finished Pile Thickness:	.116" (2.95 mm)
Dye Method:	Solution Dyed
Backing Material:	Weldlok®
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	21.0 oz. per sq. yd. (712 g/m2)
Pattern Repeat:	0.8" (W) x .75" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 8216
Pre-Consumer Recycled Content:	51.00
NSF 140:	Gold
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Wear Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------




7559
Forward Bound




7679
Jump Start



7714
Self Expressions




7822
Suit Yourself




7828
Anything Goes



7837
Go Forth



7838
Artfully Done



7928
Smart Choice



7958
Style Shaper



7959
Defining Moment



7978
Checking In