



**DESIGN**

---

|                                   |  |
|-----------------------------------|--|
| Product Type:                     | <b>Broadloom</b>                       |
| Construction:                     | <b>Tufted</b>                          |
| Minimum Sq. Yd.:                  | <b>No Minimum</b>                      |
| Surface Texture:                  | <b>Textured Multi Colored Loop</b>     |
| Gauge:                            | <b>1/10 (39.37 rows per 10 cm)</b>     |
| Density:                          | <b>3,808</b>                           |
| Weight Density:                   | <b>62,827</b>                          |
| Stitches Per Inch:                | <b>12.3 (48.43 per 10 cm)</b>          |
| Finished Pile Thickness:          | <b>.156" (3.96 mm)</b>                 |
| Dye Method:                       | <b>Solution Dyed / Yarn Dyed</b>       |
| Backing Material:                 | <b>Weldlok®</b>                        |
| Fiber Type:                       | <b>Colorstrand® Nylon</b>              |
| Face Weight:                      | <b>16.5 oz. per sq. yd. (559 g/m2)</b> |
| Pattern Repeat:                   | <b>12" (W) x 5.84" (L)</b>             |
| Width:                            | <b>12' width (3.66 m)</b>              |
| Soil Release Technology:          | <b>Sentry Soil Protection</b>          |
| Foot Traffic Recommendation TARR: | <b>Heavy</b>                           |

**SUSTAINABILITY**

---

|                                |                               |
|--------------------------------|-------------------------------|
| IAQ Green Label Plus:          | <b>Green Label Plus 8216</b>  |
| Pre-Consumer Recycled Content: | <b>52%</b>                    |
| NSF 140:                       | <b>Gold</b>                   |
| Declare Label:                 | <b>Declared Red List Free</b> |

**PERFORMANCE**

---

|                |                                       |
|----------------|---------------------------------------|
| Static:        | <b>AATCC-134 Under 3.5 KV</b>         |
| Flammability:  | <b>ASTM E 648 Class 1 (Glue Down)</b> |
| Smoke Density: | <b>ASTM E 662 Less than 450</b>       |


**SERVICE**

---


|             |  |
|-------------|--|
| Warranties: | <b>Lifetime Limited Wear Warranty, Lifetime Static</b> |
|-------------|--|



7988  
Recharge Often



7916  
Seize Challenge



7868  
Be Wise




7588  
Mind Set




7989  
Body Up




7978  
Think Positive



7896  
Just Focus



7698  
Only Believe



7299  
Dream Forward