



DESIGN

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Multi Colored Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	3,808
Weight Density:	62,827
Stitches Per Inch:	12.3 (48.43 per 10 cm)
Finished Pile Thickness:	.156" (3.96 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	Weldlok®
Fiber Type:	Colorstrand® Nylon
Face Weight:	16.5 oz. per sq. yd. (559 g/m2)
Pattern Repeat:	12" (W) x 5.84" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY


IAQ Green Label Plus:	CRI Green Label Plus GLP8216
Pre-Consumer Recycled Content:	52%
NSF 140:	Weldlok - NSF 140 Gold
Declare Label:	Declared Red List Free

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Limited Wear Warranty, Lifetime Static
-------------	--




7988
Recharge Often



7916
Seize Challenge



7868
Be Wise




7588
Mind Set




7989
Body Up




7978
Think Positive



7896
Just Focus



7698
Only Believe



7299
Dream Forward