



DESIGN

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Multi Colored Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	7,286
Weight Density:	159,852
Stitches Per Inch:	13.0 (51.18 per 10 cm)
Finished Pile Thickness:	.109" (2.77 mm)
Dye Method:	Solution Dyed
Backing Material:	Weldlok®
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	22.0 oz. per sq. yd. (746 g/m2)
Pattern Repeat:	0.8" (W) x 1.20" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY


IAQ Green Label Plus:	Green Label Plus 8216
Pre-Consumer Recycled Content:	51%
NSF 140:	Gold
Declare Label:	Declared Red List Free

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Wear Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	--



7468
Reconnect



7599
Replenish



7669
Reclaim



7831
Reinvent



7839
Reawake



7842
Rejuvenate



7848
Repurpose



7858
Rebirth



7878
Restore



7949
Refocus



7969
Restructure



7988
Revitalize