



**DESIGN**

---

|                                   |  |
|-----------------------------------|--|
| Product Type:                     | Broadloom                                    |
| Construction:                     | Tufted                                       |
| Minimum Sq. Yd.:                  | No Minimum                                   |
| Surface Texture:                  | Textured Multi Colored Loop                  |
| Gauge:                            | 1/10 (39.37 rows per 10 cm)                  |
| Density:                          | 5,625  |
| Weight Density:                   | 112,500                                      |
| Stitches Per Inch:                | 9.6 (37.80 per 10 cm)                        |
| Finished Pile Thickness:          | .128" (3.25 mm)                              |
| Dye Method:                       | Solution Dyed / Yarn Dyed                    |
| Backing Material:                 | Unibond® Plus                                |
| Fiber Type:                       | Colorstrand® Nylon                           |
| Face Weight:                      | 20.0 oz. per sq. yd. (678 g/m <sup>2</sup> ) |
| Pattern Repeat:                   | 0.4" (W) x 1.5" (L)                          |
| Width:                            | 12' width (3.66 m)                           |
| Soil Release Technology:          | Sentry Soil Protection                       |
| Foot Traffic Recommendation TARR: | Severe                                       |

**SUSTAINABILITY**

---

|                                |                              |
|--------------------------------|------------------------------|
| IAQ Green Label Plus:          | CRI Green Label Plus GLP3802 |
| Pre-Consumer Recycled Content: | 38%                          |
| NSF 140:                       | Unibond Plus - NSF 140 Gold  |
| Declare Label:                 | Declared Red List Free       |

**PERFORMANCE**

---

|                |                                |
|----------------|--------------------------------|
| Static:        | AATCC-134 Under 3.5 KV         |
| Flammability:  | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450       |


**SERVICE**

---


|             |  |
|-------------|--|
| Warranties: | Lifetime Limited Unibond® Plus Warranty, Lifetime Static |
|-------------|--|



7535  
Reflective



7575  
Life Aquatic



7585  
Color Pool




7636  
Earth's Bounty




7823  
Mountain Trail




7656  
Greenwood



7836  
Sustainable



7848  
Wilderness



7878  
Chocolate Sparkle



7838  
Satinwood



7939  
Glazed



7888  
Morning Blend



7989  
Charcoal Mix



7979  
Dawning