



**DESIGN**

|                                   |  |
|-----------------------------------|--|
| Product Type:                     | <b>Broadloom</b>                             |
| Construction:                     | <b>Tufted</b>                                |
| Minimum Sq. Yd.:                  | <b>No Minimum</b>                            |
| Surface Texture:                  | <b>Textured Patterned Multi Colored Loop</b> |
| Gauge:                            | <b>1/12 (49.00 rows per 10 cm)</b>           |
| Density:                          | <b>4,857</b>                                 |
| Weight Density:                   | <b>82,571</b>                                |
| Stitches Per Inch:                | <b>11.0 (43.31 per 10 cm)</b>                |
| Finished Pile Thickness:          | <b>.126" (3.20 mm)</b>                       |
| Dye Method:                       | <b>Solution Dyed / Yarn Dyed</b>             |
| Backing Material:                 | <b>Unibond® Plus</b>                         |
| Fiber Type:                       | <b>Colorstrand® Nylon</b>                    |
| Face Weight:                      | <b>17.0 oz. per sq. yd. (576 g/m2)</b>       |
| Pattern Repeat:                   | <b>18" (W) x 19.5" (L)</b>                   |
| Width:                            | <b>12' width (3.66 m)</b>                    |
| Soil Release Technology:          | <b>Sentry Plus</b>                           |
| Foot Traffic Recommendation TARR: | <b>Heavy</b>                                 |

**SUSTAINABILITY**


|                                |                               |
|--------------------------------|-------------------------------|
| IAQ Green Label Plus:          | <b>Green Label Plus 3802</b>  |
| Pre-Consumer Recycled Content: | <b>39.00</b>                  |
| NSF 140:                       | <b>Gold</b>                   |
| Declare Label:                 | <b>Declared Red List Free</b> |

**PERFORMANCE**


|                |                                       |
|----------------|---------------------------------------|
| Static:        | <b>AATCC-134 Under 3.5 KV</b>         |
| Flammability:  | <b>ASTM E 648 Class 1 (Glue Down)</b> |
| Smoke Density: | <b>ASTM E 662 Less than 450</b>       |

**SERVICE**


|             |   |
|-------------|---|
| Warranties: | <b>Lifetime Limited Unibond® Plus Warranty, Lifetime Static</b> |
|-------------|---|




7575  
Hypothesis Slate




7585  
Introspective Blue



7671  
Reflective Bronze




7678  
Analyzing Olive




7838  
Intellectual Beige




7853  
Insightful Greige



7855  
Dynamic Taupe



7873  
Thinking Tawny



7883  
Recognition Brown



7973  
Solution Charcoal



7975  
Cognition Grey



7989  
Synthesis Black