



DESIGN

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Multi Colored Patterned Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	6,448
Weight Density:	154,752
Stitches Per Inch:	9.6 (37.80 per 10 cm)
Finished Pile Thickness:	.134" (3.40 mm)
Dye Method:	Solution Dyed
Backing Material:	Weldlok®
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	24.0 oz. per sq. yd. (814 g/m2)
Pattern Repeat:	.60" (W) x .90" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 8216
Pre-Consumer Recycled Content:	50%
NSF 140:	Gold
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Wear Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	--



7599
Astute Solution



7769
Perfect Concept



7846
Extraordinary View




7868
Brilliant Scheme



7869
Ingenious Idea



7938
Beyond Belief



7939
Fantastic Turn



7959
Amazing Discovery



7979
Modern
Explorations