



DESIGN

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Multi Colored Patterned Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	6,968
Weight Density:	167,232
Stitches Per Inch:	10.0 (39.37 per 10 cm)
Finished Pile Thickness:	.124" (3.15 mm)
Dye Method:	Solution Dyed
Backing Material:	Weldlok®
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	24.0 oz. per sq. yd. (814 g/m2)
Pattern Repeat:	1.20" (W) x 9.60" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY


IAQ Green Label Plus:	Green Label Plus 8216
Pre-Consumer Recycled Content:	50.00
NSF 140:	Gold
Declare Label:	Declared Red List Free

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Limited Wear Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	--




7599
Astute Solution




7769
Perfect Concept




7846
Extraordinary View



7868
Brilliant Scheme




7869
Ingenious Idea



7938
Beyond Belief



7939
Fantastic Turn



7959
Amazing Discovery



7979
Modern
Explorations