



DESIGN

| | |
|-----------------------------------|---|
| Tufted Pile Weight: | 29.0 oz. per sq. yd. (983 g/m²) |
| Product Type: | Broadloom |
| Construction: | Tufted |
| Minimum Sq. Yd.: | No Minimum |
| Surface Texture: | Textured Patterned Cut and Loop |
| Gauge: | 1/12 (49.00 rows per 10 cm) |
| Density: | 6,405 |
| Weight Density: | 185,745 |
| Stitches Per Inch: | 10.3 (40.55 per 10 cm) |
| Finished Pile Thickness: | .163" (4.14 mm) |
| Dye Method: | Solution Dyed |
| Backing Material: | Unibond® Plus |
| Fiber Type: | Colorstrand® SD Nylon |
| Pattern Repeat: | 18" (W) x 23.23" (L) |
| Width: | 12' width (3.66 m) |
| Soil Release Technology: | Sentry Soil Protection |
| Foot Traffic Recommendation TARR: | Heavy |

SUSTAINABILITY

| | |
|--------------------------------|-------------------------------------|
| IAQ Green Label Plus: | CRI Green Label Plus GLP3802 |
| Pre-Consumer Recycled Content: | 39% |
| NSF 140: | Unibond Plus - NSF 140 Gold |
| Declare Label: | Declared Red List Free |

PERFORMANCE


| | |
|----------------|---------------------------------------|
| Static: | AATCC-134 Under 3.5 KV |
| Flammability: | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450 |

SERVICE


| | |
|-------------|---|
| Warranties: | Lifetime Limited Unibond® Plus Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static |
|-------------|---|




146
Harvest




258
Seasons



378
Vintage



554
Keepsake



586
Daydream



641
Spring



655
Pastoral



856
Nurture



861
Mellow