



**DESIGN**

---

|                                   |                                        |
|-----------------------------------|----------------------------------------|
| Product Type:                     | <b>Broadloom</b>                       |
| Construction:                     | <b>Tufted</b>                          |
| Minimum Sq. Yd.:                  | <b>No Minimum</b>                      |
| Surface Texture:                  | <b>Textured Patterned Cut and Loop</b> |
| Gauge:                            | <b>1/12 (49.00 rows per 10 cm)</b>     |
| Density:                          | <b>7,200</b>                           |
| Weight Density:                   | <b>208,800</b>                         |
| Stitches Per Inch:                | <b>10.5 (41.34 per 10 cm)</b>          |
| Finished Pile Thickness:          | <b>.145" (3.68 mm)</b>                 |
| Dye Method:                       | <b>Solution Dyed</b>                   |
| Backing Material:                 | <b>Unibond® Plus</b>                   |
| Fiber Type:                       | <b>Colorstrand® SD Nylon</b>           |
| Face Weight:                      | <b>29.0 oz. per sq. yd. (983 g/m2)</b> |
| Pattern Repeat:                   | <b>18" (W) x 20.57" (L)</b>            |
| Width:                            | <b>12' width (3.66 m)</b>              |
| Soil Release Technology:          | <b>Sentry Plus</b>                     |
| Foot Traffic Recommendation TARR: | <b>Heavy</b>                           |

**SUSTAINABILITY**

---

|                                |                               |
|--------------------------------|-------------------------------|
| IAQ Green Label Plus:          | <b>Green Label Plus 3802</b>  |
| Pre-Consumer Recycled Content: | <b>39.00</b>                  |
| NSF 140:                       | <b>Gold</b>                   |
| Declare Label:                 | <b>Declared Red List Free</b> |

**PERFORMANCE**


---

|                |                                       |
|----------------|---------------------------------------|
| Static:        | <b>AATCC-134 Under 3.5 KV</b>         |
| Flammability:  | <b>ASTM E 648 Class 1 (Glue Down)</b> |
| Smoke Density: | <b>ASTM E 662 Less than 450</b>       |


**SERVICE**

---


|             |                                                                                                                                                                                                     |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Warranties: | <b>Lifetime Limited Unibond® Plus Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static</b> |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|




856 Nurture




258 Seasons




378 Vintage




146 Harvest




861 Mellow




641 Spring



655 Pastoral



554 Keepsake



586 Daydream