



**DESIGN**

---

Product Type:	<b>Broadloom</b>
Construction:	<b>Tufted</b>
Minimum Sq. Yd.:	<b>No Minimum</b>
Surface Texture:	<b>Graphic Loop</b>
Gauge:	<b>1/10 (39.37 rows per 10 cm)</b>
Density:	<b>4,053</b>
Weight Density:	<b>68,901</b>
Stitches Per Inch:	<b>8.6 (33.86 per 10 cm)</b>
Finished Pile Thickness:	<b>.151" (3.84 mm)</b>
Dye Method:	<b>Solution Dyed</b>
Backing Material:	<b>Weldlok®</b>
Fiber Type:	<b>PermaStrand Olefin</b>
Face Weight:	<b>16.0 oz. per sq. yd. (542 g/m2)</b>
Pattern Repeat:	<b>2.4" (W) x 6.5" (L)</b>
Width:	<b>12' width (3.66 m)</b>
Soil Release Technology:	<b>Sentry Plus</b>
Foot Traffic Recommendation TARR:	<b>Moderate</b>

**SUSTAINABILITY**

---

IAQ Green Label Plus:	<b>Green Label Plus 1254</b>
Pre-Consumer Recycled Content:	<b>38%</b>
NSF 140:	<b>Gold</b>
Declare Label:	<b>Declared Red List Free</b>

**PERFORMANCE**


---

Static:	<b>AATCC-134 Under 3.5 KV</b>
Flammability:	<b>ASTM E 648 Class II (Glue Down)</b>
Smoke Density:	<b>ASTM E 662 Less than 450</b>


**SERVICE**

---


Warranties:	<b>10 Year Limited Wear Warranty, 10 Year Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, 10 Year Limited Static</b>
-------------	---




579  
Advocate Change



846  
Get Moving



858  
Renewed Start



862  
Resurgence



989  
Stay Positive