



DESIGN

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Graphic Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	4,053
Weight Density:	68,901
Stitches Per Inch:	8.6 (33.86 per 10 cm)
Finished Pile Thickness:	.151" (3.84 mm)
Dye Method:	Solution Dyed
Backing Material:	Weldlok®
Fiber Type:	PermaStrand Olefin
Face Weight:	16.0 oz. per sq. yd. (542 g/m2)
Pattern Repeat:	2.4" (W) x 6.5" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Moderate

SUSTAINABILITY


IAQ Green Label Plus:	Green Label Plus 1254
Pre-Consumer Recycled Content:	38%
NSF 140:	Gold
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class II (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	10 Year Limited Wear Warranty, 10 Year Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, 10 Year Limited Static
-------------	---




579
Advocate Change



846
Get Moving



858
Renewed Start



862
Resurgence



989
Stay Positive