



DESIGN

| | |
|-----------------------------------|--|
| Product Type: | Broadloom |
| Construction: | Tufted |
| Minimum Sq. Yd.: | No Minimum |
| Surface Texture: | Graphic Loop |
| Gauge: | 1/10 (39.37 rows per 10 cm) |
| Density: | 4,053 |
| Weight Density: | 68,901 |
| Stitches Per Inch: | 8.6 (33.86 per 10 cm) |
| Finished Pile Thickness: | .151" (3.84 mm) |
| Dye Method: | Solution Dyed |
| Backing Material: | Weldlok® |
| Fiber Type: | PermaStrand Olefin |
| Face Weight: | 16.0 oz. per sq. yd. (542 g/m2) |
| Pattern Repeat: | 2.4" (W) x 6.5" (L) |
| Width: | 12' width (3.66 m) |
| Soil Release Technology: | Sentry Plus |
| Foot Traffic Recommendation TARR: | Moderate |

SUSTAINABILITY

| | |
|--------------------------------|-------------------------------------|
| IAQ Green Label Plus: | CRI Green Label Plus GLP1254 |
| Pre-Consumer Recycled Content: | 38% |
| NSF 140: | Weldlok - NSF 140 Gold |
| Declare Label: | Declared Red List Free |

PERFORMANCE

| | |
|----------------|--|
| Static: | AATCC-134 Under 3.5 KV |
| Flammability: | ASTM E 648 Class II (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450 |

SERVICE


| | |
|-------------|---|
| Warranties: | 10 Year Limited Wear Warranty, 10 Year Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, 10 Year Limited Static |
|-------------|---|




579
Advocate Change



846
Get Moving



858
Renewed Start



862
Resurgence



989
Stay Positive