



**DESIGN**

---

|                                   |  |
|-----------------------------------|--|
| Tufted Pile Weight:               | 20.0 oz. per sq. yd. (678 g/m <sup>2</sup> ) |
| Product Type:                     | Broadloom                                    |
| Construction:                     | Tufted                                       |
| Minimum Sq. Yd.:                  | No Minimum                                   |
| Surface Texture:                  | Level Heathered Loop                         |
| Gauge:                            | 1/10 (39.37 rows per 10 cm)                  |
| Density:                          | 5,220  |
| Weight Density:                   | 105,966                                      |
| Stitches Per Inch:                | 9.7 (38.19 per 10 cm)                        |
| Finished Pile Thickness:          | .140" (3.56 mm)                              |
| Dye Method:                       | Solution Dyed                                |
| Backing Material:                 | Weldlok®                                     |
| Fiber Type:                       | PermaStrand Olefin                           |
| Pattern Repeat:                   | None   |
| Width:                            | 12' width (3.66 m)                           |
| Soil Release Technology:          | Sentry Plus                                  |
| Foot Traffic Recommendation TARR: | Moderate                                     |

**SUSTAINABILITY**

---

|                       |                              |
|-----------------------|------------------------------|
| IAQ Green Label Plus: | CRI Green Label Plus GLP1254 |
| NSF 140:              | Weldlok - NSF 140 Gold       |
| Declare Label:        | Declared Red List Free       |

**PERFORMANCE**


---

|                |                                 |
|----------------|---------------------------------|
| Static:        | AATCC-134 Under 3.5 KV          |
| Flammability:  | ASTM E 648 Class II (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450        |


**SERVICE**

---

|             |  |
|-------------|--|
| Warranties: | 10 Year Limited Wear Warranty, 10 Year Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, 10 Year Limited Static |
|-------------|--|




741 Sandstone




869 Calico



949 Sterling



968 Ash Gray



979 Charcoal