



DESIGN

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Multi Colored Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	5,102
Weight Density:	91,843
Stitches Per Inch:	11.3 (44.49 per 10 cm)
Finished Pile Thickness:	.127" (3.23 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	Weldlok®
Fiber Type:	Colorstrand® Nylon
Face Weight:	18.0 oz. per sq. yd. (610 g/m2)
Pattern Repeat:	.75" (W) x 1.50" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY


IAQ Green Label Plus:	Green Label Plus 8216
Pre-Consumer Recycled Content:	52%
NSF 140:	Gold
Declare Label:	Declared Red List Free

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Limited Wear Warranty, Lifetime Static
-------------	--




7579
Newton




7595
Einstein




7658
Bach




7841
Hugo




7872
Aristotle




7879
Socrates



7889
Freud



7919
Goethe



7989
Dante