



DESIGN

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	3,419
Weight Density:	58,123
Stitches Per Inch:	12.7 (50.00 per 10 cm)
Finished Pile Thickness:	.179" (4.55 mm)
Dye Method:	Solution Dyed
Backing Material:	Weldlok®
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	17.0 oz. per sq. yd. (576 g/m2)
Pattern Repeat:	4.0" (W) x 6.0" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY


IAQ Green Label Plus:	Green Label Plus 8216
Pre-Consumer Recycled Content:	52%
NSF 140:	Gold
Declare Label:	Declared Red List Free

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Wear Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	--



7194
On Target




7587
Think Smart




7698
In The Loop




7868
Moving Up




7896
Go Getter




7916
Take Charge



7973
Jump Start



7987
Just Focus



7989
Peak Awareness