



DESIGN

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	5,714
Weight Density:	114,280
Stitches Per Inch:	10.0 (39.37 per 10 cm)
Finished Pile Thickness:	.126" (3.20 mm)
Dye Method:	Solution Dyed
Backing Material:	Weldlok®
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	20.0 oz. per sq. yd. (678 g/m2)
Pattern Repeat:	1.2" (W) x 1.2" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 8216
Pre-Consumer Recycled Content:	51.00
NSF 140:	Gold

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Limited Wear Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	--



7558
Mixed Infusion



7579
Urban Indigo



7831
Golden Umbers



7848
Faded Canvas



7868
Mixed Woods



7968
Layered Earth



7989
Grounded Char