



DESIGN

| | |
|-----------------------------------|--|
| Product Type: | Broadloom |
| Construction: | Tufted |
| Minimum Sq. Yd.: | No Minimum |
| Surface Texture: | Textured Patterned Loop |
| Gauge: | 1/10 (39.37 rows per 10 cm) |
| Density: | 5,425 |
| Weight Density: | 119,350 |
| Stitches Per Inch: | 9.3 (36.61 per 10 cm) |
| Finished Pile Thickness: | .146" (3.71 mm) |
| Dye Method: | Solution Dyed / Yarn Dyed |
| Backing Material: | Weldlok® |
| Fiber Type: | Colorstrand® Nylon |
| Face Weight: | 22.0 oz. per sq. yd. (746 g/m2) |
| Pattern Repeat: | 0.8" (W) x 2.14" (L) |
| Width: | 12' width (3.66 m) |
| Soil Release Technology: | Sentry Soil Protection |
| Foot Traffic Recommendation TARR: | Severe |

SUSTAINABILITY


| | |
|--------------------------------|-------------------------------------|
| IAQ Green Label Plus: | CRI Green Label Plus GLP8216 |
| Pre-Consumer Recycled Content: | 51% |
| NSF 140: | Weldlok - NSF 140 Gold |
| Declare Label: | Declared Red List Free |

PERFORMANCE


| | |
|----------------|---------------------------------------|
| Static: | AATCC-134 Under 3.5 KV |
| Flammability: | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450 |

SERVICE


| | |
|-------------|--|
| Warranties: | Lifetime Limited Wear Warranty, Lifetime Static |
|-------------|--|



7558
Download



7579
Channel



7831
Gateway




7848
Bandwidth



7868
Bridge



7968
Connector



7989
Output