



DESIGN

Tufted Pile Weight:	22.0 oz. per sq. yd. (746 g/m2)
Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	5,425
Weight Density:	119,350
Stitches Per Inch:	9.3 (36.61 per 10 cm)
Finished Pile Thickness:	.146" (3.71 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	Weldlok®
Fiber Type:	Colorstrand® Nylon
Pattern Repeat:	0.8" (W) x 2.14" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY


IAQ Green Label Plus:	CRI Green Label Plus GLP8216
Pre-Consumer Recycled Content:	51%
NSF 140:	Weldlok - NSF 140 Gold
Declare Label:	Declared Red List Free

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Limited Wear Warranty, Lifetime Static
-------------	--------------------------------------------------------



7558
Download
Quickship Available



7579
Channel
Quickship Available



7831
Gateway
Quickship Available




7848
Bandwidth
Quickship Available



7868
Bridge
Quickship Available



7968
Connector
Quickship Available



7989
Output
Quickship Available