



**DESIGN**

---

Product Type:	<b>Broadloom</b>
Construction:	<b>Tufted</b>
Minimum Sq. Yd.:	<b>No Minimum</b>
Surface Texture:	<b>Textured Patterned Loop</b>
Gauge:	<b>1/10 (39.37 rows per 10 cm)</b>
Density:	<b>5,425</b>
Weight Density:	<b>119,350</b>
Stitches Per Inch:	<b>9.3 (36.61 per 10 cm)</b>
Finished Pile Thickness:	<b>.146" (3.71 mm)</b>
Dye Method:	<b>Solution Dyed / Yarn Dyed</b>
Backing Material:	<b>Weldlok®</b>
Fiber Type:	<b>Colorstrand® Nylon</b>
Face Weight:	<b>22.0 oz. per sq. yd. (746 g/m2)</b>
Pattern Repeat:	<b>0.8" (W) x 2.14" (L)</b>
Width:	<b>12' width (3.66 m)</b>
Soil Release Technology:	<b>Sentry Plus</b>
Foot Traffic Recommendation TARR:	<b>Severe</b>

**SUSTAINABILITY**

---

IAQ Green Label Plus:	<b>Green Label Plus 8216</b>
Pre-Consumer Recycled Content:	<b>51.00</b>
NSF 140:	<b>Gold</b>
Declare Label:	<b>Declared Red List Free</b>

**PERFORMANCE**


---

Static:	<b>AATCC-134 Under 3.5 KV</b>
Flammability:	<b>ASTM E 648 Class 1 (Glue Down)</b>
Smoke Density:	<b>ASTM E 662 Less than 450</b>


**SERVICE**

---


Warranties:	<b>Lifetime Limited Wear Warranty, Lifetime Static</b>
-------------	--



7558  
Download



7579  
Channel



7831  
Gateway




7848  
Bandwidth



7868  
Bridge



7968  
Connector



7989  
Output