



DESIGN

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	7,111
Weight Density:	133,776
Stitches Per Inch:	11.3 (44.49 per 10 cm)
Finished Pile Thickness:	.081" (2.66 mm)
Dye Method:	Solution Dyed
Backing Material:	Unibond® Plus
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	16.0 oz. per sq. yd (542 g/m2)
Pattern Repeat:	18" (W) x 19" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY


IAQ Green Label Plus:	Green Label Plus 3802
Pre-Consumer Recycled Content:	38.00
NSF 140:	Gold

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class I (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Unibond® Plus Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



152
Morphed Macramé




358
Reshaped Felt




751
Art Cloth



859
Found Object



862
Fiber Collage



883
Organic Textile



955
Bespoke Fabric



983
Wrapped Shibori



999
Tooled Surface