



**DESIGN**

|                                   |                                       |
|-----------------------------------|---------------------------------------|
| Product Type:                     | <b>Broadloom</b>                      |
| Construction:                     | <b>Tufted</b>                         |
| Minimum Sq. Yd.:                  | <b>No Minimum</b>                     |
| Surface Texture:                  | <b>Textured Patterned Loop</b>        |
| Gauge:                            | <b>1/12 (47.00 rows per 10 cm)</b>    |
| Density:                          | <b>6,776</b>                          |
| Weight Density:                   | <b>108,416</b>                        |
| Stitches Per Inch:                | <b>12.0 (47.24 per 10 cm)</b>         |
| Finished Pile Thickness:          | <b>.085" (2.16 mm)</b>                |
| Dye Method:                       | <b>Solution Dyed</b>                  |
| Backing Material:                 | <b>Unibond® Plus</b>                  |
| Fiber Type:                       | <b>Colorstrand® SD Nylon</b>          |
| Face Weight:                      | <b>16.0 oz. per sq. yd (542 g/m2)</b> |
| Pattern Repeat:                   | <b>18" (W) x 18" (L)</b>              |
| Width:                            | <b>12' width (3.66 m)</b>             |
| Soil Release Technology:          | <b>Sentry Plus</b>                    |
| Foot Traffic Recommendation TARR: | <b>Heavy</b>                          |

**SUSTAINABILITY**

|                                |                              |
|--------------------------------|------------------------------|
| IAQ Green Label Plus:          | <b>Green Label Plus 3802</b> |
| Pre-Consumer Recycled Content: | <b>38%</b>                   |
| NSF 140:                       | <b>Gold</b>                  |

**PERFORMANCE**

|                |                                       |
|----------------|---------------------------------------|
| Static:        | <b>AATCC-134 Under 3.5 KV</b>         |
| Flammability:  | <b>ASTM E 648 Class I (Glue Down)</b> |
| Smoke Density: | <b>ASTM E 662 Less than 450</b>       |

**SERVICE**

|             |   |
|-------------|---|
| Warranties: | <b>Lifetime Limited Unibond® Plus Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static</b> |
|-------------|---|



152  
Morphed Macramé



358  
Reshaped Felt



751  
Art Cloth



859  
Found Object



862  
Fiber Collage



883  
Organic Textile



955  
Bespoke Fabric



983  
Wrapped Shibori



999  
Tooled Surface