



DESIGN

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Multi Colored Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	5,347
Weight Density:	80,205
Stitches Per Inch:	12.3 (48.43 per 10 cm)
Finished Pile Thickness:	.101" (2.57 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	Weldlok®
Fiber Type:	Colorstrand® Nylon
Face Weight:	15.0 oz. per sq. yd. (509 g/m2)
Pattern Repeat:	0.8" (W) x 0.00" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY


IAQ Green Label Plus:	Green Label Plus 8216
Pre-Consumer Recycled Content:	52%
NSF 140:	Gold

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	10 Year Limited Wear Warranty, 10 Year Static
-------------	--




358
Scientist




689
Architect




859
Composer




862
Educator



883
Scholar




884
Philosopher



955
Archaeologist



983
Mathematician



999
Writer