



**DESIGN**

---

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	6,712
Weight Density:	147,664
Stitches Per Inch:	10.0 (39.37 per 10 cm)
Finished Pile Thickness:	.118" (3.00 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Colorstrand® Nylon
Face Weight:	22.0 oz. per sq. yd. (746 g/m2)
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	Monolithic, VerticalAshlar, BrickAshlar, QuarterTurn
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Severe

**SUSTAINABILITY**

---

IAQ Green Label Plus:	Green Label Plus 1098
Pre-Consumer Recycled Content:	47%
NSF 140:	Gold
Declare Label:	Declared

**PERFORMANCE**

---

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450


**SERVICE**

---


Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Static
-------------	--



7565  
Blue Ridge



7588  
Boston Harbor



7828  
Sun Valley



7839  
Gulf Coast




7847  
DuPont Circle




7848  
Grand Canyon



7852  
Painted Desert



7856  
Goldengate Bridge



7872  
Amelia Island



7876  
Redwood Forest



7878  
Big Sur



7948  
Mineral Springs



7968  
Stone Mountain



7988  
Pikes Peak