

DESIGN

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Level Multi Colored Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	6,000
Weight Density:	96,000
Stitches Per Inch:	10.7 (42.13 per 10 cm)
Finished Pile Thickness:	.096" (2.44 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Colorstrand® Nylon
Face Weight:	16.0 oz. per sq. yd. (543 g/m2)
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	QuarterTurn
Soil Release Technology:	Sentry Plus
GSA Stain Release Rating:	Pass
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 1098
Pre-Consumer Recycled Content:	48.00
NSF 140:	Gold
Declare Label:	Declared

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Static
-------------	--------------------------------------------------------




7579
Newton




7595
Einstein




7658
Bach




7841
Hugo




7872
Aristotle




7879
Socrates



7889
Freud



7919
Goethe



7989
Dante