



**DESIGN**

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	4,418
Weight Density:	59,645
Stitches Per Inch:	8.5 (33.46 per 10 cm)
Finished Pile Thickness:	.110" (2.79 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	13.5 oz. per sq. yd. (457 g/m2)
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	QuarterTurn, VerticalAshlar
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Heavy

**SUSTAINABILITY**

IAQ Green Label Plus:	Green Label Plus 1098
Pre-Consumer Recycled Content:	48%
NSF 140:	Gold
Declare Label:	Declared

**PERFORMANCE**


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

**SERVICE**


Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	--



7589  
Indigo




7843  
Camel



7858  
Khaki



7878  
Taupe



7885  
Chocolate



7949  
Slate



7967  
Charcoal



7979  
Ebony