



**DESIGN**

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Level Heathered Loop
Gauge:	1/8 (31.50 rows per 10 cm)
Density:	7,105
Weight Density:	106,579
Stitches Per Inch:	8.8 (34.65 per 10 cm)
Finished Pile Thickness:	.076" (1.93 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	15.0 oz. per sq. yd. (509 g/m2)
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	QuarterTurn
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Severe

**SUSTAINABILITY**

IAQ Green Label Plus:	Green Label Plus 1098
Pre-Consumer Recycled Content:	48%
NSF 140:	Gold
Declare Label:	Declared

**PERFORMANCE**

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

**SERVICE**


Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	--



7335  
Rosarita Rose




7373  
Aurora Red




7408  
Viridian Sea



7509  
Blueprint Ink




7510  
Ocean Wave



7554  
Floral Tapestry




7559  
Anodized Lapis



7565  
Mineral Quartz



7589  
Celestial



7679  
Blarney Stone



7714  
Silvery Nickel



7719  
Carbon Char



7818  
Coffee Espresso



7837  
Biscotti Crunch



7843  
Desert Oasis



7866  
Earthed Fields



7928  
Majolica Tin



7978  
Mineralite