



DESIGN

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Level Heathered Loop
Gauge:	1/8 (31.50 rows per 10 cm)
Density:	7,105
Weight Density:	106,579
Stitches Per Inch:	8.8 (34.65 per 10 cm)
Finished Pile Thickness:	.076" (1.93 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	15.0 oz. per sq. yd. (509 g/m2)
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	QuarterTurn
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 1098
Pre-Consumer Recycled Content:	48%
NSF 140:	Gold
Declare Label:	Declared

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	--



7335
Rosarita Rose




7373
Aurora Red




7408
Viridian Sea



7509
Blueprint Ink




7510
Ocean Wave



7554
Floral Tapestry




7559
Anodized Lapis



7565
Mineral Quartz



7589
Celestial




7679
Blarney Stone



7714
Silvery Nickel



7719
Carbon Char



7818
Coffee Espresso



7837
Biscotti Crunch



7843
Desert Oasis



7866
Earthed Fields



7928
Majolica Tin



7978
Mineralite