



DESIGN

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Multi Colored Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	6,110
Weight Density:	113,037
Stitches Per Inch:	10.5 (41.34 per 10 cm)
Finished Pile Thickness:	.109" (2.74 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	18.5 oz. per sq. yd.
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	VerticalAshlar, MultiDirectional, Monolithic, BrickAshlar, QuarterTurn
Soil Release Technology:	Sentry
GSA Stain Release Rating:	Pass
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY


IAQ Green Label Plus:	Green Label Plus 1098
Pre-Consumer Recycled Content:	48%
NSF 140:	Gold
Declare Label:	Declared

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	--



7356
Meadow Grass



7379
Ember




7546
Flora



7568
Tributary



7579
Big Sky



7721
Birchbark



7861
North Woods



7876
Timber



7889
Woodland



7939
Ravine



7958
Echo Valley



7965
River View