



DESIGN

Tufted Pile Weight:	14.0 oz. per sq. yd. (474 g/m2)
Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Level Patterned Loop
Gauge:	1/12 (49.00 rows per 10 cm)
Density:	5,040
Weight Density:	70,560
Stitches Per Inch:	9.3 (36.61 per 10 cm)
Finished Pile Thickness:	.100" (2.54 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Colorstrand® SD Nylon
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	Monolithic, Quarter Turn, Vertical Ashlar, Brick Ashlar, Multi Directional
GSA Stain Release Rating:	Pass
Stain Release Technology:	Sentry Plus Stain Protection
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY


IAQ Green Label Plus:	CRI Green Label Plus GLP1098
Pre-Consumer Recycled Content:	48%
NSF 140:	EcoFlex ICT - NSF 140 Gold
Declare Label:	Declared

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	---




7238
Pumice
Quickship Available




7358
Breccia




7559
Opal
Quickship Available




7568
Marble
Quickship Available



7656
Gabbro




7688
Ore



7728
Chert
Quickship Available



7858
Feldspar



7879
Basalt



7927
Shale



7948
Granite
Quickship Available