



**DESIGN**

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Level Patterned Loop
Gauge:	1/12 (49.00 rows per 10 cm)
Density:	5,040
Weight Density:	70,560
Stitches Per Inch:	9.3 (36.61 per 10 cm)
Finished Pile Thickness:	.100" (2.54 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	14.0 oz. per sq. yd. (474 g/m2)
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	Monolithic, QuarterTurn, VerticalAshlar, BrickAshlar, MultiDirectional
Soil Release Technology:	Sentry Plus
GSA Stain Release Rating:	Pass
Foot Traffic Recommendation TARR:	Heavy

**SUSTAINABILITY**


IAQ Green Label Plus:	Green Label Plus 1098
Pre-Consumer Recycled Content:	48%
NSF 140:	Gold
Declare Label:	Declared

**PERFORMANCE**

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

**SERVICE**


Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	--




7238  
Pumice




7358  
Breccia




7559  
Opal




7568  
Marble



7656  
Gabbro




7688  
Ore



7728  
Chert



7858  
Feldspar



7879  
Basalt



7927  
Shale



7948  
Granite