



DESIGN

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Multi Colored Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	5,414
Weight Density:	108,280
Stitches Per Inch:	9.3 (36.61 per 10 cm)
Finished Pile Thickness:	.133" (3.38 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Colorstrand® Nylon
Face Weight:	20.0 oz. per sq. yd. (678 g/m2)
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	QuarterTurn, BrickAshlar, VerticalAshlar, Monolithic
Soil Release Technology:	Sentry Plus
GSA Stain Release Rating:	Pass
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 1098
Pre-Consumer Recycled Content:	45.00
Post-Consumer Recycled Content:	1.00
NSF 140:	Gold
Declare Label:	Declared

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Static
-------------	--



7535
Reflective



7575
Life Aquatic



7585
Color Pool




7636
Earth's Bounty




7823
Mountain Trail




7656
Greenwood



7836
Sustainable



7848
Wilderness



7868
Autumn Harvest



7878
Chocolate Sparkle



7838
Satinwood



7875
Covert Brown



7939
Glazed



7888
Morning Blend



7989
Charcoal Mix



7979
Dawning