



**DESIGN**

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Multi Colored Loop
Gauge:	1/12 (49.00 rows per 10 cm)
Density:	4,400
Weight Density:	72,600
Stitches Per Inch:	11.0 (43.31 per 10 cm)
Finished Pile Thickness:	.135" (3.43 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Colorstrand® Nylon
Face Weight:	16.5 oz. per sq. yd. (559 g/m2)
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	Monolithic, VerticalAshlar, BrickAshlar, QuarterTurn
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Heavy

**SUSTAINABILITY**


IAQ Green Label Plus:	Green Label Plus 1098
Pre-Consumer Recycled Content:	48.00
NSF 140:	Gold
Declare Label:	Declared

**PERFORMANCE**


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

**SERVICE**

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Static
-------------	--



7575 Hypothesis Slate



7585 Introspective Blue



7671 Reflective Bronze




7678 Analyzing Olive




7838 Intellectual Beige




7853 Insightful Greige



7855 Dynamic Taupe



7873 Thinking Tawny



7883 Recognition Brown



7973  
Solution Charcoal



7975  
Cognition Grey



7989  
Synthesis Black