



DESIGN

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Multi Colored Loop
Gauge:	1/12 (49.00 rows per 10 cm)
Density:	4,708
Weight Density:	80,031
Stitches Per Inch:	12.0 (47.24 per 10 cm)
Finished Pile Thickness:	.130" (3.30 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Colorstrand® Nylon
Face Weight:	17.0 oz. per sq. yd. (576 g/m2)
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	VerticalAshlar, QuarterTurn, Monolithic, BrickAshlar
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 1098
Pre-Consumer Recycled Content:	48%
NSF 140:	Gold
Declare Label:	Declared

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Static
-------------	--




7575
Hypothesis Slate



7585
Introspective Blue



7671
Reflective Bronze




7678
Analyzing Olive



7838
Intellectual Beige




7853
Insightful Greige



7855
Dynamic Taupe



7873
Thinking Tawny



7883
Recognition Brown



7973
Solution Charcoal



7975
Cognition Grey



7989
Synthesis Black