



DESIGN

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Level Patterned Loop
Gauge:	1/12 (49.00 rows per 10 cm)
Density:	6,486
Weight Density:	129,730
Stitches Per Inch:	10.0 (39.37 per 10 cm)
Finished Pile Thickness:	.111" (2.82 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	20.0 oz. per sq. yd. (678 g/m2)
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	BrickAshlar, QuarterTurn
Soil Release Technology:	Sentry Soil Protection
GSA Stain Release Rating:	Pass
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY


IAQ Green Label Plus:	Green Label Plus 1098
Pre-Consumer Recycled Content:	48%
NSF 140:	Gold
Declare Label:	Declared

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------




7721
Globetrotter




7938
Travelogue




7956
Getaway




7137
Picturesque




7868
Overlook




7889
Landscape



7676
Terrace



7585
Seascape



7989
Peninsula



7746
Wanderer