



**DESIGN**

|                                   |  |
|-----------------------------------|--|
| Tufted Pile Weight:               | <b>20 oz. per sq. yd. (678.2 g/m<sup>2</sup>)</b>              |
| Product Type:                     | <b>Tile</b>  |
| Construction:                     | <b>Tufted</b>  |
| Minimum Sq. Yd.:                  | <b>No Minimum</b>  |
| Surface Texture:                  | <b>Textured Patterned Loop</b>                                 |
| Gauge:                            | <b>1/8 (31.50 rows per 10 cm)</b>                              |
| Density:                          | <b>6,207</b>   |
| Weight Density:                   | <b>124,140</b>   |
| Stitches Per Inch:                | <b>9.8 (38.58 per 10 cm)</b>                                   |
| Finished Pile Thickness:          | <b>.116" (2.95 mm)</b>   |
| Dye Method:                       | <b>Solution Dyed</b>   |
| Backing Material:                 | <b>EcoFlex ICT</b>   |
| Fiber Type:                       | <b>Colorstrand® SD Nylon</b>                                   |
| Pattern Repeat:                   | <b>Not Applicable</b>  |
| Size:                             | <b>24" x 24" (.6096 m x .6096 m)</b>                           |
| Installation Method:              | <b>Monolithic, Vertical Ashlar, Brick Ashlar, Quarter Turn</b> |
| Stain Release Technology:         | <b>Sentry Plus Stain Protection</b>                            |
| Soil Release Technology:          | <b>Sentry Soil Protection</b>                                  |
| Foot Traffic Recommendation TARR: | <b>Heavy</b>   |

**SUSTAINABILITY**

|                                |                                     |
|--------------------------------|-------------------------------------|
| IAQ Green Label Plus:          | <b>CRI Green Label Plus GLP1098</b> |
| Pre-Consumer Recycled Content: | <b>48%</b>                          |
| NSF 140:                       | <b>EcoFlex ICT - NSF 140 Gold</b>   |
| Declare Label:                 | <b>Declared</b>                     |

**PERFORMANCE**

|                |                                       |
|----------------|---------------------------------------|
| Static:        | <b>AATCC-134 Under 3.5 KV</b>         |
| Flammability:  | <b>ASTM E 648 Class 1 (Glue Down)</b> |
| Smoke Density: | <b>ASTM E 662 Less than 450</b>       |

**SERVICE**

|             |   |
|-------------|---|
| Warranties: | <b>Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static</b> |
|-------------|---|




7138  
Very Curry




7145  
Sandrift Beige




7241  
Sundried Tomato



7465  
Bombshell Red




7489  
Velvet Underground



7559  
Slaten Sky  
Quickship Available



7575  
Voltaic Blue



7599  
Twilight Dawn  
Quickship Available



7646  
Wacky Khaki



7652  
Spring Leaf



7846  
Bamboo Sprout  
Quickship Available




7847  
Stoney Pebble  
Quickship Available



7858  
Natural Hybrid



7868  
Coffee Bean



7869  
Grounded Earth



7898  
Double Latte  
Quickship Available



7938  
Moon Eclipse



7939  
Hammered Tin  
Quickship Available



7959  
Chameleon Mixer  
Quickship Available



7968  
Burnished Iron  
Quickship Available




7969  
Chimney Sweep



7979  
Metal Works



7988  
Pencil Point



7989  
Blackened Pearl  
Quickship Available