





DESIGN


Tufted Pile Weight:	17.0 oz. per sq. yd. (576 g/m2)
Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	6,059
Weight Density:	103,003
Stitches Per Inch:	11.5 (45.28 per 10 cm)
Finished Pile Thickness:	.101" (2.57 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Colorstrand® Nylon
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	Monolithic, VerticalAshlar, BrickAshlar, QuarterTurn, MultiDirectional
Soil Release Technology:	Sentry Soil Protection
GSA Stain Release Rating:	Pass
Foot Traffic Recommendation TARR:	Severe




7131
Madras
Quickship Available



7585
Sea Breeze
Quickship Available



7878
Mudslide
Quickship Available



7968
Smoky Martini
Quickship Available



7989
Black Velvet
Quickship Available

SUSTAINABILITY

IAQ Green Label Plus:	CRI Green Label Plus GLP1098
Pre-Consumer Recycled Content:	44%
NSF 140:	EcoFlex ICT - NSF 140 Gold
Declare Label:	Declared

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Static
-------------	---