



DESIGN

Tufted Pile Weight:	15.0 oz. per sq. yd. (509 g/m2)
Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	4,576
Weight Density:	68,644
Stitches Per Inch:	10.0 (39.37 per 10 cm)
Finished Pile Thickness:	.118" (3.00 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Colorstrand® SD Nylon
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	VerticalAshlar, QuarterTurn, MultiDirectional, BrickAshlar, Monolithic
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY

IAQ Green Label Plus:	CRI Green Label Plus GLP1098
Pre-Consumer Recycled Content:	48%
NSF 140:	EcoFlex ICT - NSF 140 Gold
Declare Label:	Declared

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	---



152
Living Fast




358
Thrill Seeker



751
Dare Devil



859
Glory Days



862
Tough Guy



883
Wild Thing



955
Cool Hand



983
Roust About



999
Leather Jacket