



**DESIGN**

Tufted Pile Weight:	<b>15.0 oz. per sq. yd. (509 g/m2)</b>
Product Type:	<b>Tile</b>
Construction:	<b>Tufted</b>
Minimum Sq. Yd.:	<b>No Minimum</b>
Surface Texture:	<b>Textured Multi Colored Loop</b>
Gauge:	<b>1/10 (39.37 rows per 10 cm)</b>
Density:	<b>4,286</b>
Weight Density:	<b>64,209</b>
Stitches Per Inch:	<b>10.6 (41.73 per 10 cm)</b>
Finished Pile Thickness:	<b>.126" (3.20 mm)</b>
Dye Method:	<b>Solution Dyed / Yarn Dyed</b>
Backing Material:	<b>EcoFlex ICT</b>
Fiber Type:	<b>Colorstrand® Nylon</b>
Pattern Repeat:	<b>Not Applicable</b>
Size:	<b>24" x 24" (.6096 m x .6096 m)</b>
Installation Method:	<b>QuarterTurn</b>
Soil Release Technology:	<b>Sentry Soil Protection</b>
Foot Traffic Recommendation TARR:	<b>Heavy</b>

**SUSTAINABILITY**


IAQ Green Label Plus:	<b>CRI Green Label Plus GLP1098</b>
Pre-Consumer Recycled Content:	<b>48%</b>
NSF 140:	<b>EcoFlex ICT - NSF 140 Gold</b>
Declare Label:	<b>Declared</b>

**PERFORMANCE**


Static:	<b>AATCC-134 Under 3.5 KV</b>
Flammability:	<b>ASTM E 648 Class 1 (Glue Down)</b>
Smoke Density:	<b>ASTM E 662 Less than 450</b>

**SERVICE**


Warranties:	<b>Lifetime Limited Carpet Tile Warranty, Lifetime Static</b>
-------------	---




358  
Scientist  
Quickship Available




689  
Architect  
Quickship Available




859  
Composer  
Quickship Available




862  
Educator  
Quickship Available




883  
Scholar  
Quickship Available




884  
Philosopher  
Quickship Available



955  
Archaeologist  
Quickship Available



983  
Mathematician  
Quickship Available



999  
Writer  
Quickship Available