



DESIGN

| | |
|-----------------------------------|---------------------------------|
| Product Type: | Tile |
| Construction: | Tufted |
| Minimum Sq. Yd.: | No Minimum |
| Surface Texture: | Textured Multi Colored Loop |
| Gauge: | 1/10 (39.37 rows per 10 cm) |
| Density: | 4,286 |
| Weight Density: | 64,209 |
| Stitches Per Inch: | 10.6 (41.73 per 10 cm) |
| Finished Pile Thickness: | .126" (3.20 mm) |
| Dye Method: | Solution Dyed / Yarn Dyed |
| Backing Material: | EcoFlex ICT |
| Fiber Type: | Colorstrand® Nylon |
| Face Weight: | 15.0 oz. per sq. yd. (509 g/m2) |
| Pattern Repeat: | Not Applicable |
| Size: | 24" x 24" (.6096 m x .6096 m) |
| Installation Method: | QuarterTurn, VerticalAshlar |
| Soil Release Technology: | Sentry Plus |
| Foot Traffic Recommendation TARR: | Heavy |

SUSTAINABILITY


| | |
|--------------------------------|-----------------------|
| IAQ Green Label Plus: | Green Label Plus 1098 |
| Pre-Consumer Recycled Content: | 48% |
| NSF 140: | Gold |
| Declare Label: | Declared |

PERFORMANCE


| | |
|----------------|--------------------------------|
| Static: | AATCC-134 Under 3.5 KV |
| Flammability: | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450 |

SERVICE


| | |
|-------------|--|
| Warranties: | Lifetime Limited Carpet Tile Warranty, Lifetime Static |
|-------------|--|




358
Scientist




689
Architect




859
Composer




862
Educator




883
Scholar




884
Philosopher



955
Archaeologist



983
Mathematician



999
Writer