



**DESIGN**

Tufted Pile Weight:	<b>15.0 oz. per sq. yd. (509 g/m2)</b>
Product Type:	<b>Tile</b>
Construction:	<b>Tufted</b>
Minimum Sq. Yd.:	<b>No Minimum</b>
Surface Texture:	<b>Textured Multi Colored Loop</b>
Gauge:	<b>1/10 (39.37 rows per 10 cm)</b>
Density:	<b>4,286</b>
Weight Density:	<b>64,209</b>
Stitches Per Inch:	<b>10.6 (41.73 per 10 cm)</b>
Finished Pile Thickness:	<b>.126" (3.20 mm)</b>
Dye Method:	<b>Solution Dyed / Yarn Dyed</b>
Backing Material:	<b>EcoFlex ICT</b>
Fiber Type:	<b>Colorstrand® Nylon</b>
Pattern Repeat:	<b>Not Applicable</b>
Size:	<b>24" x 24" (.6096 m x .6096 m)</b>
Installation Method:	<b>QuarterTurn, VerticalAshlar</b>
Soil Release Technology:	<b>Sentry Soil Protection</b>
Foot Traffic Recommendation TARR:	<b>Heavy</b>

**SUSTAINABILITY**


IAQ Green Label Plus:	<b>CRI Green Label Plus GLP1098</b>
Pre-Consumer Recycled Content:	<b>48%</b>
NSF 140:	<b>EcoFlex ICT - NSF 140 Gold</b>
Declare Label:	<b>Declared</b>

**PERFORMANCE**


Static:	<b>AATCC-134 Under 3.5 KV</b>
Flammability:	<b>ASTM E 648 Class 1 (Glue Down)</b>
Smoke Density:	<b>ASTM E 662 Less than 450</b>

**SERVICE**


Warranties:	<b>Lifetime Limited Carpet Tile Warranty, Lifetime Static</b>
-------------	---




**358**  
Scientist  
Quickship Available




**689**  
Architect  
Quickship Available




**859**  
Composer  
Quickship Available




**862**  
Educator  
Quickship Available




**883**  
Scholar  
Quickship Available




**884**  
Philosopher  
Quickship Available



**955**  
Archaeologist  
Quickship Available



**983**  
Mathematician  
Quickship Available



**999**  
Writer  
Quickship Available