



DESIGN

| | |
|-----------------------------------|--|
| Product Type: | Tile |
| Construction: | Tufted |
| Minimum Sq. Yd.: | No Minimum |
| Surface Texture: | Textured Patterned Loop |
| Gauge: | 1/12 (47.00 rows per 10 cm) |
| Density: | 8,704 |
| Weight Density: | 141,005 |
| Stitches Per Inch: | 10.0 (39.37 per 10 cm) |
| Finished Pile Thickness: | .067" (1.70 mm) |
| Dye Method: | Solution Dyed |
| Backing Material: | EcoFlex ICT |
| Fiber Type: | Colorstrand® SD Nylon |
| Face Weight: | 16.0 oz. per sq. yd. (542 g/m2) |
| Pattern Repeat: | Not Applicable |
| Size: | 12" x 36" (.3048 m x .9144 m) |
| Installation Method: | Monolithic, HalfLap, BrickAshlar, BasketWeave, PlankHalfLap, MonolithicStepping, Random, Herringbone |
| Soil Release Technology: | Sentry Plus |
| Foot Traffic Recommendation TARR: | Heavy |

SUSTAINABILITY


| | |
|--------------------------------|-----------------------|
| IAQ Green Label Plus: | Green Label Plus 1098 |
| Pre-Consumer Recycled Content: | 48.00 |
| NSF 140: | Gold |
| Declare Label: | Declared |

PERFORMANCE


| | |
|----------------|--------------------------------|
| Static: | AATCC-134 Under 3.5 KV |
| Flammability: | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450 |

SERVICE


| | |
|-------------|---|
| Warranties: | Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty |
|-------------|---|




152
Rugged Range
Metallic



358
Classic Ridge
Metallic



751
Perfect Paths
Metallic




859
Downing Stone
Metallic



862
Canyon Clay
Metallic



883
Wild Terrain
Metallic



955
Solid Ground
Metallic



983
Clean Slate
Metallic



999
Daring Drift
Metallic