



DESIGN

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	8,704
Weight Density:	141,005
Stitches Per Inch:	10.0 (39.37 per 10 cm)
Finished Pile Thickness:	.067" (1.70 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	16.0 oz. per sq. yd. (542 g/m2)
Pattern Repeat:	Not Applicable
Size:	12" x 36" (.3048 m x .9144 m)
Installation Method:	Monolithic, HalfLap, BrickAshlar, BasketWeave, PlankHalfLap, MonolithicStepping, Random, Herringbone
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY


IAQ Green Label Plus:	Green Label Plus 1098
Pre-Consumer Recycled Content:	48%
NSF 140:	Gold
Declare Label:	Declared

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty
-------------	---




152
Rugged Range
Metallic




358
Classic Ridge
Metallic



751
Perfect Paths
Metallic




859
Downing Stone
Metallic



862
Canyon Clay
Metallic



883
Wild Terrain
Metallic



955
Solid Ground
Metallic



983
Clean Slate
Metallic



999
Daring Drift
Metallic