



### DESIGN

Tufted Pile Weight:	16.0 oz. per sq. yd. (542 g/m <sup>2</sup> )
Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	7,200
Weight Density:	116,640
Stitches Per Inch:	11.0 (43.31 per 10 cm)
Finished Pile Thickness:	.081" (2.05 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Colorstrand® SD Nylon
Pattern Repeat:	Not Applicable
Size:	12" x 36" (.3048 m x .9144 m)
Installation Method:	Monolithic, HalfLap, BrickAshlar, BasketWeave, PlankHalfLap, MonolithicStepping, Random, Herringbone
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Heavy

### SUSTAINABILITY


IAQ Green Label Plus:	CRI Green Label Plus GLP1098
Pre-Consumer Recycled Content:	46%
NSF 140:	EcoFlex ICT - NSF 140 Gold
Declare Label:	Declared

### PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

### SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	--



152  
Rugged Range  
Quickship Available



358  
Classic Ridge  
Quickship Available




751  
Perfect Paths  
Quickship Available



859  
Downing Stone  
Quickship Available



862  
Canyon Clay  
Quickship Available



883  
Wild Terrain  
Quickship Available



955  
Solid Ground  
Quickship Available



983  
Clean Slate  
Quickship Available



999  
Daring Drift  
Quickship Available